## Honda BigWing —EXCITES THE WORLD—

Honda Motorcycle and Scooter India Pvt. Ltd.,

Registered Office: Plot No. 1, Sector - 03, IMT Manesar, Distt. Gurugram (Haryana) – 122050, India Customer Care: customercare@honda2wheelersindia.com Website: www.hondabigwing.in



Follow us on: Honda BigWing India | Market BigWingIndia









## LIGHTWEIGHT NIMBLE

Built to go the distance and genuine comfort matters – for two, so it's good to be prepared. Handling is light, nimble and confidence inspiring, from dirt tracks to green lanes, long-travel Showa suspension absorbs bumps, while the front and rear wheel combination roll smoothly over rough terrain. An 850mm seat height and 208kg kerb weight make the TRANSALP easy to manage from walking pace upwards; the riding position is relaxed yet sits you upright, offering great visibility and natural comfort.





ride and full LED lighting features Emergency Stop Signal (ESS) technology to alert road users behind of sudden braking.







## TECHNICAL SPECIFICATIONS

BODY DIMENSIONS	
Dimensions (LxWxH)	2325mm X 838mm X 1450mm
Wheel Base	1560mm
Ground Clearance	212mm
Kerb Weight	208kg
Seat Height	850mm
Fuel Tank Capacity	16.9L
TYRES	
Tyre Size & Type (front)	90/90-21M/C (54H)
Tyre Size & Type (Rear)	150/70R18M/C (70H)
BRAKES	
Break Size & Front	Dual 310mm Disc
Break Size & Rear	Single 256mm Disc
Braking System	2 Channel ABS
FRAMES & SUSPENSIONS	
Frame type	Diamond (steel pipe)

Telescopic / Swing arm (ProLink)

ENGINE	
Туре	OHC(Uni-cam) liquid-cooled inline two-cylinder
Displacement	755cc
Max Power	67.5kW @ 9500rpm
Max Torque	75N-m @ 7250 rpm
Fuel System	Fuel Injection
Bore x Stroke	87.0 x 63.5
Compression ratio	11.0 + 2
Valve System	8 Valve
No. of cyclinders	2

TRANSMISSION	
Starting method	Self
Clutch Type	Wet multiplate assist and slipper clutch
No. of Gears	6

ECTRICALS	
attery rating (Ah)	12V, 9.1Ah
ead lamp/ tail lamp	LED